



[Cables](#)

[LAN Cabling](#)







[About WW](#)





[Contact](#)

[Home](#)







RG Coaxial Cables Catalog


MIL-C-17 & MIL-DTL-17 Non-Plenum Cable -40+80C	MIL-C-17 & MIL-DTL-17 High-Temp Cables -55+200C	MIL-Type Custom-made and Special Cables
<small>BC = Bare Copper TC = Tin Coated Copper CCS = Copper Covered Steel SPC = Silver Plated Copper SCCS = Silver plated Copper Covered Steel NC = Non-Contaminating PVC = Polyvinyl Chloride PTFE = Poly Tetra Flour Ethylene FEP = Fluorinated Ethylene Propylene LSOH = Low Smoke Zero Halogen</small>		

	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG00800	RG-8/u	52	13# Stranded BC 7x0.724mm	PE 7.24mm	Single Braid BC 97%	Black PVC 10.3mm
	WRG00801	RG-8A/u	52	13# Stranded BC 7x0.724mm	PE 7.24mm	Single Braid BC 97%	Black NC PVC 10.3mm
	WRG00900	RG-9B/u	50	13# Stranded SPC 7x0.724mm	PE 7.24mm	Double Braid SPC 97%	Black NC PVC 10.7mm
	WRG01100	M17/6- RG011	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 97%	Black NC PVC 10.3mm
	WRG01101	RG-11/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 96%	Black PVC 10.3mm
	WRG01102	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 96%	Black NC PVC 10.3mm








	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG01103	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 86%	Black NC PVC 10.3mm
	WRG01104	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 95%	LSOH 10.3mm -40+80C
	WRG01105	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 95%	Black NC PVC 10.3mm -40+105C
	WRG01106	Modified M17/181- 00001	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Al. Foil + Braid TC 95%	Black NC PVC 10.3mm


	WRG01107	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 95%	Black NC PVC + Outdoor PE Jacket 14.0mm
	WRG01108	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid BC 95%	Black NC PVC + Outdoor MB Jacket 14.8mm
	WRG01109	RG-11A/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Single Braid CCA 89%	Black PVC 10.3mm -20+80C
	WRG05500	RG-55/u	53.5	20# Solid BC 0.813mm	PE 2.95mm	Double Braid TC 96%	Transparent PE 5.3mm
	WRG05501	RG-55B/u	53.5	20# Solid SPC 0.813mm	PE 2.95mm	Double Braid TC 95%+94%	Black PE 5.05mm
	WRG05800	M17/28-RG058	50	20# Stranded TC 19x0.18mm	PE 2.95mm	Single Braid TC 95%	Black NC PVC 4.95mm








	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG05801	RG-58C/u	50	20# Stranded TC 19x0.18mm	PE 2.95mm	Single Braid TC 95%	Black NC PVC 4.95mm
	WRG05802	RG-58/u	53.5	20# Solid BC 0.813mm	PE 2.95mm	Single Braid TC 95%	Black PVC 4.9mm
	WRG05803	RG-58A/u	50	20# Stranded TC 19x0.18mm	PE 2.95mm	Single Braid TC 95%	Black NC PVC 4.9mm
	WRG05811	RG-58A/u	50	20# Stranded TC 19x0.18mm	PE 2.95mm	Single Braid 86%	Black NC PVC 4.9mm
	WRG05900	M17/29-RG059	75	23# Solid CCS 0.574mm	PE 3.71mm	Single Braid 95%	Black NC PVC 6.15mm
	WRG05901	RG-59B/u	75	23# Solid CCS 0.574mm	PE 3.71mm	Single Braid BC 95%	Black NC PVC 6.15mm






	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG05902	RG-59B/u	75	23# Solid CCS 0.574mm	PE 3.71mm	Single Braid BC 86%	Black NC PVC 6.15mm




	WRG05903	RG-59B/u	75	23# Solid CCS 0.574mm	PE 3.71mm	Single Braid BC 94%	Black LSOH 6.15mm
	WRG05904	RG-59B/u	75	23# Solid CCS 0.574mm	PE 3.71mm	Single Braid BC 94%	Black NC PVC 6.15mm
	WRG05915	RG-59B/u	75	23# Solid CCS 0.574mm	PE 3.71mm	Single Braid CCA 86%	Black NC PVC 6.00mm
	WRG06200	M17/30- RG062	93	22# Solid CCS 0.64mm	PE AS 3.71mm	Single Braid BC 95%	Black NC PVC 6.15mm
	WRG06201	RG-62/u	93	22# Solid CCS 0.635mm	PE AS 3.71mm	Single Braid BC 95%	Black PVC 6.15mm
	WRG06202	RG-62B/u	93	24# Stranded CCS 7x0.203mm	PE AS 3.71mm	Single Braid BC 95%	Black PVC 6.15mm
	WRG06300	M17/31- RG-063	125	22# Solid CCS 0.635mm	PE AS 7.24mm	Single Braid BC 96%	Black NC PVC 10.3mm
	WRG07100	M17/90- RG-071	93	22# Solid CCS 0.635mm	PE AS 3.71mm	Double Braid BC/TC 98%	Black PE 6.25mm







	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG12200	M17/157- RG-122/u	50	22# Stranded TC 27x0.127mm	PE 2.44mm	Single Braid TC 95%	Black NC PVC 4.05mm
	WRG14100	RG-141A/u	50	18# Solid SCCS 0.94mm	PTFE 2.95mm	Single Braid SPC 95%	Brown Fiberglass 4.75mm -55+250C
	WRG14200	M17/60- RG-142	50	18# Solid SCCS 0.94mm	PTFE 2.95mm	Double Braid SPC 96%	Brown Tint FEP 4.95mm
	WRG14201	M17/158 RG-142B/u	50	18# Solid SCCS 0.94mm	PTFE 2.95mm	Double Braid SPC 96%	Brown Tint FEP 4.95mm
	WRG14203	RG-142B/u	50	18# Solid SCCS 0.94mm	PTFE 2.95mm	Double Braid SPC 96%	Grey FEP 4.95mm
	WRG14204	RG-142B/u	50	18# Solid SCCS 0.94mm	PTFE 2.95mm	Double Braid SPC 96%	Black FEP 4.95mm
	WRG17400	RG-174/u	50	26# Stranded CCS 7x0.16mm	PE 1.52mm	Single Braid TC 95%	Black NC PVC 2.54mm






	WRG174xx	RG-174/u	50	26# Stranded CCS 7x0.16mm	PE 1.52mm	Single Braid TC 95%	Colored PVC 2.54mm
---	--------------------------	----------	----	---------------------------------	--------------	------------------------	-----------------------


	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG17800	M17/169 RG-178B/u	50	30# Stranded SCCS 7x0.102mm	PTFE 0.84mm	Single Braid SPC 96%	White FEP 1.83mm
	WRG17801	M17/93- RG-178	50	30# Stranded SCCS 7x0.102mm	PTFE 0.84mm	Single Braid SPC 96%	White FEP 1.83mm
	WRG17900	M17/94- RG-179	75	30# Stranded SCCS 7x0.102mm	PTFE 1.60mm	Single Braid SPC 95%	Brown Tint FEP 2.54mm
	WRG18000	M17/95- RG-180	95	30# Stranded SCCS 7x0.102mm	PTFE 2.61mm	Single Braid SPC 95%	Brown Tint FEP 3.55mm
	WRG18700	RG-187A/u	75	30# Stranded SCCS 7x0.102mm	PTFE 1.52mm	Single Braid SPC 95%	White PTFE Tape 2.7mm -55+250C
	WRG18800	RG-188A/u	50	26# Stranded SCCS 7x0.17mm	PTFE 1.52mm	Single Braid SPC 96%	White PTFE Tape 2.7mm -55+250C
	WRG19500	RG-195A/u	95	30# Stranded SCCS 7x0.102mm	PTFE 2.60mm	Single Braid SPC 96%	White PTFE Tape 3.7mm -55+250C

	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG19600	RG-196A/u	50	30# Stranded SCCS 7x0.102mm	PTFE 0.86mm	Single Braid SPC 96%	White PTFE Tape 1.83mm -55+250C
	WRG21200	M17/162 RG-212/u	50	15# Solid SPC 1.41mm	PE 4.70mm	Double Braid SPC 95%	Black NC PVC 8.45mm
	WRG21300	M17/163 RG-213/u	50	13# Stranded BC 7x0.724mm	PE 7.24mm	Single Braid BC 97%	Black NC PVC 10.3mm
	WRG21302	M17/163 RG-213/u	50	13# Stranded BC 7x0.724mm	PE 7.24mm	Single Braid BC 94%	Black NC PVC 10.3mm
	WRG21400	M17/164 RG-214/u	50	13# Stranded SPC 7x0.724mm	PE 7.24mm	Double Braid SPC 97%	Black NC PVC 10.8mm

	WRG21401	M17/164 RG-214/u	50	13# Stranded SPC 7x0.724mm	PE 7.24mm	Double Braid SPC 81+85%	Black NC PVC 10.8mm
	WRG21402	M17/75 RG214	50	13# Stranded SPC 7x0.724mm	PE 7.24mm	Double Braid SPC 81+85%	Black NC PVC 10.8mm
	WRG21600	M17/77 RG-216/u	75	18# Stranded TC 7x0.404mm	PE 7.24mm	Double Braid BC 95%	Black NC PVC 10.8mm

	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG21700	RG-217/u	50	10# Solid BC 2.7mm	PE 9.4mm	Double Braid BC 95%	Black NC PVC 13.8mm
	WRG22300	M17/167 RG-223/u	50	19# Solid SPC 0.86mm	PE 2.95mm	Double Braid SPC 96%	Black NC PVC 5.4mm
	WRG30200	M17/110- RG-302	75	22# Solid SCCS 0.64mm	PTFE 3.71mm	Single Braid SPC 96%	Brown Tint FEP 5.1mm
	WRG30300	M17/111- RG-303	50	18# Solid SCCS 1.00mm	PTFE 2.95mm	Single Braid SPC 96%	Brown Tint FEP 4.3mm
	WRG31600	M17/172- RG-316/u	50	26# Stranded SCCS 7x0.17mm	PTFE 1.52mm	Single Braid SPC 96%	White FEP 2.6mm
	WRG31601	M17/113- RG-316	50	26# Stranded SCCS 7x0.17mm	PTFE 1.52mm	Single Braid SPC 96%	Brown Tint FEP 2.6mm

	WW P/N	CABLE	Impedance Ohm	Inner Conductor	Dielectric	Outer Conductor	Jacket
	WRG31602	M17/152- RG-316DS	50	26# Stranded SCCS 7x0.17mm	PTFE 1.52mm	Double Braid SPC 96%	Brown Tint FEP 2.9mm
	WRG39300	M17/127- RG-393	50	8# Stranded SPC 7x0.79mm	PTFE 7.24mm	Double Braid SPC 96%	Brown Tint FEP 9.9mm
	WRG39301	M17/174- RG-393	50	8# Stranded SPC 7x0.79mm	PTFE 7.24mm	Double Braid SPC 96%	Brown Tint FEP 9.9mm
	WRG40000	M17/128- RG-400	50	20# Stranded SPC 19x0.203mm	PTFE 2.94mm	Double Braid SPC 96%	Brown Tint FEP 4.95mm
	WRG40001	M17/175- RG-400	50	20# Stranded SPC 19x0.203mm	PTFE 2.94mm	Double Braid SPC 96%	Brown Tint FEP 4.95mm

	WRG40300	M17/131- RG-403	50 Triaxial	30# Stranded SCCS 7x0.102mm	PTFE 0.84mm	Double Braid SPC 96% With interlayer	Brown Tint FEP 2.95mm
---	-----------------	--------------------	----------------	-----------------------------------	----------------	---	-----------------------------

Passive components. Active people.™

Cables	LAN Cabling	About WW	Contact	Home
------------------------	-----------------------------	--------------------------	-------------------------	----------------------